




## Flaw Detection UT8000

Portable ultrasound flaw detector for different types of material and components. Delivering fully traceable inspection data and rapid report creation.



### Swiss Quality

Swiss Quality for unmatched performance and ruggedness. A unit that can meet the most demanding environment and requirements.



### Enhanced Productivity

No adaptation time needed: learn within 1 hour and start your inspection with the most intuitive, user-friendly, feature-rich, intelligent software



### Peace of Mind

The unique Rewind and log-book functions record and secure set-ups and inspection results, enabling on-demand assessment of inspection parameters. Including GPS locations, photos of the components and even audio messages.



## Proceq Flaw Detector App Tech Specs

<b>Automated calibration</b>	Velocity, zero offset
<b>Test modes</b>	Pulse echo, dual, through transmission or grid
<b>Units</b>	Millimeters, inches, or microseconds
<b>Range</b>	3 – 11760 mm at 5900 m/s
<b>Velocity</b>	100 – 10000 m/s
<b>Zero offset</b>	0 – 50 mm
<b>Display delay</b>	up to full range
<b>Refracted angle</b>	0° – 90° in 1° increments
<b>Gates</b>	2x, fully independent
<b>Alarms</b>	Positive and negative threshold/curve
<b>Measurement display</b>	Up to 5 locations (manual or auto selection)
<b>Echo-to-echo</b>	Standard gate 2 – gate 1
<b>Measurement</b>	DAC / TCG / AVG(DGS) / AWS / CSC
<b>Languages</b>	English, German, Italian, French, Spanish, Chinese, Japanese, Korean, Russian, Turkish



## Instrument Tech Specs

<b>Configuration</b>	1 UT channel
<b>Transducer Socket</b>	Lemo 00
<b>Pulse Voltage</b>	100 to 400 V (square pulse)
<b>PRF</b>	10 – 2000 Hz
<b>Gain Range</b>	0-110 dB
<b>Bandwidth</b>	0.2 - 20MHz
<b>Display</b>	Any Compatible Apple iPad® 8.3 to 12.9 Inches
<b>Memory</b>	Up to 2 TB (depending on the iPad model)
<b>Connections</b>	Encrypted Wi-Fi connection to iPad USB-C cable to iPad
<b>Signal Enhancement</b>	Digital and analogue filters, rejection, averaging
<b>Digitizing Frequency</b>	125 MHz
<b>Supported Scans</b>	A-Scan, B-Scan, Grid
<b>Report Generation</b>	Indication table, HTML export
<b>Encoder</b>	6 PIN Lemo, B-Scan
<b>Battery</b>	Removable pack, 6x AA (NIMH), flight-safe
<b>Autonomy</b>	5 Hrs
<b>Damping</b>	50, 400 Ω
<b>Pulse width</b>	Adjustable; 25 – 2500 nsec
<b>Weight</b>	698 g, incl. battery pack 1.54 lbs incl. battery pack
<b>Input / Output</b>	1 USB-C charging 1 USB-C data connection
<b>IP rating</b>	IP67
<b>Shock tested</b>	MIL STD 810 H Meth 516.8 Proc. II
<b>Vibration Test</b>	MIL STD 810 H Meth. 514.8 Proc. I Cat. 4
<b>Norm</b>	BS EN 12668-1 Certificate ISO 22232-1 Certificate ASTM E317

Standards & Guidelines	Description
ASTM E317 - 16	
EN 12668-1	

---

SWISS  MADE



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.  
[www.screeningeagle.com](http://www.screeningeagle.com)

[Request a quote](#)



