




## Manual Film Applicators

# ZAF 2010

---

### 4-sided Applicator Frame

---



#### Versatility

The applicator frame can be used manually or in combination with automatic film applicators. Various width and thickness combinations (4 per version) are available.



#### Reliability

A significant advantage that the coating material being applied is retained within the guide walls, resulting in clean and precise applications.



#### Ease of Use

The film thickness can be easily chosen by placing the applicator with the desired thickness.



## Instrument Tech Specs

	4 gap heights depending on version: 30 / 60 / 90 / 120 $\mu\text{m}$ (1.18 / 2.36 / 3.54 / 4.72 mil)
<b>Measurement Modes</b>	50 / 100 / 150 / 200 $\mu\text{m}$ (1.97 / 3.94 / 5.91 / 7.87 mil) or 4 on request from 5 - 2,000 $\mu\text{m}$ (0.20 - 78.74 mil)
<b>Measuring Geometries</b>	Film Width depending on version: 60 mm (2.36") 80 mm (3.15") or on request from 20 mm to 200 mm (0.79" - 7.87")

## Our Accessories

Image	PartNumber	Description
	43010923	Proceq Precision-Vacuumpate with a series of holes of 1 mm (0.04") drilling (43010923) Accessories
	43010966	Proceq Precision-Vacuumpate with a series of holes of 0.5 mm (0.02") drilling (43010966) Accessories
	43010906	Proceq Vacuum Pump 230 V with hose (43010906) Accessories
	43010924	Proceq Vacuum Pump 115 V with hose (43010924) Accessories

Standards & Guidelines	Description
ASTM D1640 (Depending on accessory)	
ASTM D4748-10	
ASTM D823	

SWISS  MADE



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.  
[www.screeningeagle.com](http://www.screeningeagle.com)

[Request a quote](#)



